

P.T.O.

1500 r.p.m. - IP 23 4 poles Brushless - AVR

GA AGRIPLUS 1-30



Technical data

		Three-phase 400V - 50Hz	Mono-phase 230V - 50Hz
Power	kVA	30	12
Active power	kW	24	9.6
Current	%	87.6	
Gear box	Ratio	1:3.5	
Driving power	kW	29	
Tractor power	HP	92	
P.T.O. speed	r.p.m.	430	
P.T.O. sizing Cardan	Nm	956	
	kW	54	
Dimensions (LxWxH)	Mm	1135 x 640 x 915	
Weight	Kg	228	



Environmental conditions

Temperature	°C	25
Relative humidity	%	30
Maximum altitude	Mt	1000



EQUIPMENT

Alternator stabilized, high performance
Gear box
Raised chassis
3-point-connection frame
Control panel
EC Protections

CONTROL PANEL ON BOARD

Digital instrument:

- Voltmeter
- Frequencymeter
- Ammeter
- Hour counter

Protections

Single phase thermal protection
4-pole magnetothermic switch
Differential protection (Id=0,03A)
2 pole magnetothermic switch
IP65 cover

Outputs

1 CEE 400V (3P+N+E) 63A
1 CEE 230V (2P+E) 32A
1 Schuko



DOCUMENTATION

User and maintenance manual
EC Declaration of Conformity

APPLICATIONS



AGRICULTURAL

