


P.T.O.
3000 r.p.m. - IP 23 2 poles Compound

GA AGRIPLUS 3-31

Technical data

		Three-phase 400V - 50Hz	Mono-phase 230V - 50Hz
Power	kVA	31.5	12.4
Active power	kW	25.2	9.92
Current	%	86	
Gear box	Ratio	1:6.9	
Driving power	kW	30.2	
Tractor power	HP	95	
P.T.O. speed	r.p.m.	430	
P.T.O. sizing Cardan	Nm	995	
	kW	56	
Dimensions (LxWxH)	Mm	1135 x 640 x 915	
Weight	Kg	190	



Environmental conditions

Temperature	°C	25
Relative humidity	%	30
Maximum altitude	Mt	1000

EQUIPMENT

Alternator stabilized, high performance
 Gear box
 Raised chassis
 3-point-connection frame
 Control panel
 EC Protections

CONTROL PANEL ON BOARD

Digital instrument:

- Voltmeter
 - Frequencymeter
 - Ammeter
 - Hour counter

Protections

2-pole magnetothermic switch
 4-pole magnetothermic switch
 Differential protection (Id=0,03A)
 IP65 cover

Outputs

1 CEE 400V (3P+N+E) 63A
 1 CEE 230V (2P+E) 16A



DOCUMENTATION

User and maintenance manual
 EC Declaration of Conformity

APPLICATIONS



AGRICULTURAL

